

BENNING CM P1 CM P2

TRUE RMS Mini Current Clamp Meters

Recommended retail price:

86,90 €

All prices are exclusive of VAT.
Item no.: 044678

TRUE RMS Mini Current Clamp Meters Pocket-Size

BENNING CM P1, CM P2 TRUE RMS Mini Current Clamp Meters

- minimum dimensions, maximum safety
- precise measurements of load currents of up to 400 A
- TRUE RMS measuring method
- inrush current measurement (INRUSH) of motors and lighting systems
- low-pass filter (LPF) to suppress high-frequency pulses
- Volt sensor (NCV) for non-contact signaling of phase voltages
- maximum clamp opening 23 mm
- memory of measured value (HOLD)
- delivery including high quality protection carrying case



NEW!
TRUE RMS
Mini Current Clamp Meters

Recommended retail price:

119,70 €

All prices are exclusive of VAT.
Item no.: 044679



TRUE
RMS

400 A
AC/DC

Auflösung
10 mA
Resolution

Inrush

LPF

CAT III
600 V

LCD

LCD

dupol@benning.de • Tel.: +49 / (0) 2871 / 93-111

www.benning.de

original size



BENNING CM P1/CM P2

TRUE RMS Mini Current Clamp Meters

Application:

Due to their compact design and low weight, the new miniature current measuring clamps fit into any pocket. They are small, handy and always ready to use.

- precise measurements of load currents of up to 400 A
- inrush current measurement (INRUSH) of motors and lighting systems
- low-pass filter (LPF, approx. 160 Hz) to suppress high-frequency pulses at pulsed motor drives

Measuring functions

- TRUE RMS AC current measurement up to 400 A (CM P1/P2)
- DC current measurement up to 400 A (CM P2)
- Volt sensor (NCV) for non-contact signaling of phase voltages

Features

- TRUE RMS measuring method
- maximum resolution of 10 mA in the 40.00 A measuring range
- LC display with illumination
- memory of measured value (HOLD) and zero setting button (Δ , CM P2)
- automatic range switching, automatic switch-off (APO after 15 min., can be disabled) and low battery indication
- measuring category CAT III 600 V
- delivery including protection carrying case

| Technical data | BENNING CM P1/CM P2 |
|----------------------------|--|
| display: | 4 digits LCD, illuminated |
| current (AC): | 40.00 mA/ 400.0 A, TRUE RMS |
| max. resolution/ accuracy: | 10 mA/ $\pm 2\%$ of reading + 5 digits |
| memory function: | HOLD |
| clamp opening max.: | 23 mm |
| automatic switch-off: | 15 min., can be disabled |
| dimensions/ weight: | 149 x 59 x 27 mm/140 g |
| measuring category: | CAT III 600 V |
| scope of delivery: | incl. 2 x 1.5 V batteries (IEC LR03) and carrying case |

| | BENNING CM P1 |
|---------------------------|---------------|
| item no. | 044678 |
| recommended retail price: | 86.90 € |

| | BENNING CM P2 |
|----------------------------|--|
| current (DC): | 40.00 mA/ 400.0 A |
| max. resolution/ accuracy: | 10 mA/ $\pm 2\%$ of reading + 5 digits |
| item no.: | 044679 |
| recommended retail price: | 119.70 € |

Your specialist dealer:

BENNING

BENNING Elektrotechnik und Elektronik GmbH & Co. KG
 Münsterstraße 135-137 • D-46397 Bocholt
 Tel.: + 49 / (0) 2871 / 93-111 • Fax: + 49 / (0) 2871 / 93-429
 www.benning.de • E-Mail: duspol@benning.de